

Inteligentna Elektronika

Ul. Raduńska 36A
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



BARCO

Nazwa

HD-40 40" rugged large display for collaborative visualization

Cena

0,00 zł

Producent

Barco

OPIS PRODUKTU

Screen size

40"

Resolution

HD 1080 (1920x1080px)

Brightness

Typical 400 cd/m² (116 fL)

Contrast ratio

2000:1 (in dark environment)

Dimming ratio

minimum 150:1 (from daylight readability to night conditions)

Vibration

Ships: MIL-STD-167-1, Type 1

Shock

MIL-STD-810F Meth. 516.4 | 30g - 12.5ms half sine

MIL-STD-901D, Class I, Medium weight Grade B

Operating temperature

MIL-STD-810E

Low temp: 0°C

High temp: +50°C

Storage temperature

MIL-STD-810E

Low temp: -40°C

High temp: +70°C

Humidity

MIL-STD-810E

Max. 95% @ 40°C

Operating altitude Low pressure

MIL-STD-810E

15,000 ft

EMI / EMC

MIL-STD-461 F (Surface navy applications)

FCC

FCC-A

Signal inputs

DVI-I, VGA (type DVI-I, integrated DVI)

Video-over-IP (optional)

RS-232 serial port

9 PIN sub D

Power

MS 27656 T 09 F 98P (MIL-C-39999 series I)

Controls

UP / DOWN / SEL / QUIT / STANDBY In conjunction with OSD

Indicators

Green 'Power' LED, Red 'Fault' LED

Power Supply

115-220V AC

Guidelines

MIL-STD-1399 compliant section 300A

Power consumption

240W (typical)

Safety

IEC 950

Weight

33.6 kg (74 lbs)

Finishing

Bezel color is No 37038 (FED-STD-595), lusterless black

MTTR

Less than 30 minutes

Scaling

No scaling / full screen / keep aspect

AutoSet, Automatic Phase Adjust (APA), Automatic Gain Control (AGC)

Options

Video-over-IP via fiber or copper Ethernet