
Inteligentna Elektronika

Ul. Raduńska 36A
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl

**BARCO**

Nazwa

Nio 5MP MDNG-51215 MegaPixel (2048 x 2560) diagnostic grayscale display system

Cena

0,00 zł

Producent

Barco

OPIS PRODUKTU

Screen technology

TFT AM LCD Dual Domain IPS

Active screen size (diagonal)

541 mm (21.3")

Active screen size (H x V)

422 x 338 mm (16.5 x 13.3")

Aspect ratio (H:V)

5:4

Resolution

5MP (2560 x 2048)

Pixel pitch

0.1650 mm

Active screen height

337.9 mm (13.3")

Color imaging

No

Gray imaging

Yes

Number of grayscales (LUT in/LUT out)

10 bit

Viewing angle (H, V)

170°

Uniform Luminance Technology (ULT)

No

Per Pixel Uniformity (PPU)

No

Ambient Light Compensation (ALC)

No
Backlight Output Stabilization (BLOS)
Yes
I-Guard
No
Maximum luminance
700 cd/m²
DICOM calibrated luminance (ULT off)
500 cd/m²
Contrast ratio (ULT off)
800:1
Response time (Tr + Tf)
25 ms
Video input signals
DVI-D Dual Link
USB ports
1 upstream (endpoint), 2 downstream
USB standard
1.1
Power consumption (nominal)
95W
Power save mode
Yes
Dimensions with stand (W x H x D)
Portrait: 382 x 577~637 x 249 mm
Landscape: 488 x 472~532 x 249 mm
Dimensions w/o stand (W x H x D)
Portrait: 382x 488 x 114 mm
Landscape: 488 x 382 x x 114 mm
Net weight with stand
13.5 kg
Mounting standard
VESA (100 mm)
Screen protection
Protective, non-reflective PMMA cover
Recommended modalities
CT, MR, US, DR, CR, NM, Film
Certifications
CE, UL60601, CSA C22.2 No 601.1, IEC60601, EN 60601-1-2, FDA 510k, FCC level B
Supplied accessories
Getting Started Guide
Quick-Installation Sheet
Video cable (DVI Dual Link)
Main cables (UK, European (CEBEC/KEMA), USA (UL/CSA; adaptor plug NEMA 5-15P), Chinese (CCC))
USB 2.0 cable
External power supply
Optional accessories
NA
QA software
MediCal QAWeb
Warranty
5 years