

Inteligentna Elektronika

Ul. Raduńska 36A
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



BARCO

Nazwa

**OverView OLSF-521 Fully redundant 50"
full HD 16:9 LED video wall with front
access and 3D**

Cena

0,00 zł

Producent

Barco

OPIS PRODUKTU

Resolution

Full HD (1920 x 1080px)

Brightness

on-screen: 440/355 Cd/m² in 2D/3D

On-screen contrast

560,000:1

Color

Up to 165% EBU (at maximum color mode)

Display technology

Rear projection DLP

White point

3,200/6,500/9,600/arbitrary

Screen

FXS, with H/V 34°/33° (+/- 3°) half gain angle

Screen gap

Hor: 1.8 mm | 0.07", Vert. 1.5 mm | 0.06" (@ 25°C)

Color stability

Self calibration with spectrometer based Sense6

Dimensions

• Width: 1,088 mm | 42.8"

• Height: 612 mm | 24.1"

• Depth: 454 mm | 17.9"

• Weight: Projection Module: < 53 kg | 117 lbs

Light source

6x redundancy for each of 3 LED's

Light source lifetime

> 60,000h (at 6500k)

> 80,000h (eco mode)

MTBF LED > 500,000 h

Power

350W (max)

230W (typ.)

170W (eco)

Signal

2x Dual link DVI in / 2x Dual link DVI out

Signal processing

Loop through

Free cropping, free scaling (optional)

Direct ethernet access

Built in web server

Accessibility & servicing

Front

Integration to third party equipment

WEB service API

Stereoscopic 3D

yes

Conditions for operation

10°C - 40°C, 50°F - 104°F, 80% humidity (non-condensing)

Heat dissipation

580 BTU/h (eco)

785 BTU/h (typ.)

1,194 BTU/h (max)

Warranty

2 years