

Inteligentna Elektronika

Ul. Raduńska 36A
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



BARCO

Nazwa

**OverView OVL-715 Fully redundant 70"
SXGA+ 4:3 LED video wall**

Cena

0,00 zł

Producent

Barco

OPIS PRODUKTU

Resolution

SXGA+ (1400x1050px)

On-screen contrast

1,200,000 :1

Color

Up to 165% EBU

Display technology

rear-projection DLP

White point

3,200K | 6,500K | 9,600K | arbitrary

Brightness uniformity

Typ 95% ANSI 13

Screen

BB, FXS, High Gain

Screen gap

< 0.2 mm | 0.008" stitched

< 1.5 mm | 0.06" modular (@25°C)

< 0.4 mm | 0.015" modular (@30°C)

Color stability

Self calibrating with spectrometer based Sense6

Dimensions

• Diagonal: 70" nominal

• Width: 1,400 mm / 55.1"

• Height: 1,050 mm / 41.3"

• Depth: 899 mm / 35.4"

• Aspect ratio: 4:3

• Weight/module 101.5 kg / 224 lbs

Light source
3x six fold redundant LED block
Light source lifetime
> 60,000 h, > 80,000 h (eco)
Conditions for operation
10°C-40°C, 50°F-104°F, 80% humidity (nc)
AC input voltage
90 – 240 V, 50-60Hz
Power
typical: 230W, maximum: 350W, eco mode: 170W
Heat dissipation
typical: 785, maximum: 1,194, eco mode: 580 BTU/h
Direct ethernet access
Build in web server
Graphical user interface
All settings and operational parameters
Signal input/output
2x Dual link DVI in, 2x Dual link DVI out
Single link DVI in, with HDCP (optional)
Pixel clock
320 MHz
Input frequency
24 – 62 Hz
Genlock
49 – 61 Hz
Signal processing
Loop through up to 10 cubes / Free cropping, free scaling
Integration to third party equipment
Web based API
Warranty
2 years