

Inteligentna Elektronika

Ul. Raduńska 36A
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl

CHRISTIE®



Nazwa

**Przełącznik matrycowy Christie Vista
URS-1608 Universal-Routing-Switcher
(124-002103-XX)**

Cena

265 000,00 zł

Producent

Christie

OPIS PRODUKTU

Input - Number

Vista URS-0808: 8 inputs total - 4 supporting composite, S-video, component analog, HDSDI, SDI, and 3G SDI (SMPTE 424M) and 4 supporting progressive DVI and progressive RGBHV

Vista URS-1608: 16 inputs total - 8 supporting composite, S-video, component analog, HDSDI, SDI, and 3G SDI (SMPTE 424M) and 8 supporting progressive DVI and progressive RGBHV

Input - Signals

Analog RGB composite, component DVI, single-link and dual-link (8 inputs are dual-link capable)
SDI, HD-SDI and 3G HD-SDI (SMPTE 424M)

Input - Resolutions

Up to 2560 x 1600 (any resolution greater than 2048 x 1200 uses 2 input channels)

Output - Number

8 @ (< 2048x1200) or 4 @(2560x1600) or combination

Output - Signals

Analog RGB, component DVI, single-link and dual-link (4 outputs are dual-link capable)
SDI, HD-SDI and 3G HD-SDI (SMPTE 424M)

Output - Resolutions

Up to 2560 x 1600 (any resolution greater than 2048 x 1200 uses 2 output channels)

Pixel Clock

Analog up to 165MHz, DVI up to 265MHz

Scan Rates

Up to 120Hz dependant on pixel clock rate maximum

Control & Networking

RS232 In/Out

Ethernet (10/100)

Enhanced Feature Sets

Independent aspect ratio and frame rate setup, overlay's, transitions, aspect ratio conversions, integrated source monitoring, built-in image capture, output rotation (portrait), optional stereoscopic support

Accessories

Standard: User Manual (CD_ROM and quick manual), 2 AC power cords, URS control software, rack hardware

Power Requirements

Operating Voltage: 100 VAC to 240 VAC @ 50/60 Hz

Max Current: 9.0 A @100VAC

Max Power: 900 W

Dissipation:

Dimensions

Size:4RU

Dimensions:(L x W x H): 21.9 x 17.3 x 7.0" (556 x 439 x 178 mm)

Shipping Dimensions:(LxWxH) 32.3 x 25.5 x 15.0" (820 x 648 x 381mm)

Volume: 2652 cubic in

Weight: 59 lb (27 kg)

Shipping Weight: 70.5 lb (32 kg)

Operating Environment

Temp: 5 to 35° C (40 to 95° F)

Humidity: 20 - 80% non-condensing

Regulatory

This product conforms to the following regulations related to product safety, environmental requirements and electromagnetic compatibility (EMC):

UL/CSA/IEC 60950 (3rd Edition)

FCC Class A, CE, CCC

RoHS, WEE

Limited Warranty

1 year parts and labor

Contact an authorized Christie representative for full details of our limited warranty